

SC01-TD-W0601

Smart POS Terminal



ZKTeco introduces the **SC01-TD-W0601** series, a comprehensive point-of-sale system. This series includes three models, each with a dual display and an all-in-one design. The modular design also consists of an MSR reader (optional) and an RFID reader (optional) for convenient payment and improved retail experience. Moreover, the SC01-TD-W0601 series has a fanless system with an innovative heat pipe design that supports long operating hours.

Features

- All-in-one POS with 15.6" True-Flat PCAP Touch Screen, HD & FHD LCD Screen
- Modular Design and Optionally Embedded with MSR & RFID Reader for Convenient Payment
- Hidden Cable Management for Sleek Design
- Fanless System with Innovative Heat Pipe Design to Avoid the Spread of Grease and Heat within the POS Terminal

Applications



Retail Outlets



Restaurants



Cafes



coffee shops



More

spec if cations

Model	SC01-TD-W0603-4030-8C		SC01-TD-W0605-10210-8C	SC01-TD-W0605-10210-10LCD
CPU	Intel®Core®i3-4030U @ 2.40GHz		Intel®Core®i5-10210UU@ 1.7GHz	Intel®Core®i5-10210UU@ 1.7GHz
Memory	4GB RAM (Standard), DDR3 & DDR4, up to 8GB 64GB SSD (Standard), up to 512GB			
Display	Configuration 1: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive TouchScreen; Second: LED (8Cdigital tube) Configuration 2: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive TouchScreen; Second: VFD (2*20 lines) Configuration 3: Main: 15.6" HD, 1366*768 (Optional: FHD 1920*1080), Capacitive TouchScreen; Second: 11.6" HD, 1366*768			
Material	ABS plastic			
Colour	Black and Gray, White (Optional)			
Operating System	Supported Windows System 7, 8, 10, 11			
Dimension	345*180*354mm			
Packing Dimension	385*240*415mm			
Net Weight	Configuration 1&2: 4.7Kg Configuration 3: 5.6Kg			
Gross Weight	Configuration 1&2: 5Kg Configuration 3: 5.9Kg			
Interface (s)	1* USB 3.0 5* USB 2.0 1* COM port 1* VGA port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port	4* USB 3.0 2* USB 2.0 2* COM port 1* VGA port 1* HDMI port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port	4* USB 3.0 2* USB 2.0 2* COM port 1* VGA port 1* HDMI port 1* RJ45 LAN port 1* Audio jack 1* MIC IN 1* Power port	
Power Supply	DC12V/5A			
Wi-Fi (Optional)	IEEE 802.11 a/b/g/n/ 2.4GHz (Single-band) IEEE 802.11 a/b/g/n/ 2.4GHz /5GHz (Dual-band)			
Bluetooth	Not Support			
Speaker	2*2W (Optional)			
Peripherals (Optional)	Built-in MSR reader Built-in RFID reader			
Operating Humidity	20% to 80% RH (Non-condensing)			
Storage Humidity	20% to 80% RH (Non-condensing)			
Operating Temperature	0°C to 40°C			
Storage Temperature	-15°C to 60°C			
Certification (s)	ISO9001, CE, FCC, RoHS			

