

### > CARACTERÍSTICAS

| Type                                              | 2C×16AWG Power-Limited Fire Cable |
|---------------------------------------------------|-----------------------------------|
| Specification                                     | UL1424                            |
| <b>Conductor</b>                                  |                                   |
| Conductor material                                | BC                                |
| Conductor Construction (mm)                       | 1×1.29±0.01                       |
| <b>Insulation</b>                                 |                                   |
| Insulation material                               | SR-PVC                            |
| Insulation diameter(mm)                           | 1.7±0.1                           |
| Average Thickness (mm)                            | 0.20                              |
| Min Thickness (mm)                                | 0.16                              |
| Color                                             | Red,Black                         |
| <b>Rip Cord</b>                                   |                                   |
| Rip Cord                                          | Yes                               |
| <b>Jacket</b>                                     |                                   |
| Jacket material                                   | PVC                               |
| Jacket Diameter(mm)                               | 4.3±0.2                           |
| Average Thickness (mm)                            | 0.43                              |
| Min Thickness (mm)                                | 0.38                              |
| Color                                             | Red                               |
| <b>Electrical &amp; Physical Characteristics:</b> |                                   |
| Conductor DCR 20°C                                | ≤13.5Ω/KM                         |
| Operating Temperature Range                       | -20°C~+75°C                       |
| Max. Operating Voltage                            | 300V (not for power purposes)     |
| Smoke And Fire                                    | FPLR                              |



16AWG X 2C - PVC - UL

