



> CARACTERÍSTICAS

- Control inteligente de la CPU
- Reinicio automático mientras se recupera la corriente alterna
- Regulador de voltaje activo (AVR) con función de elevación y reducción para la estabilización del voltaje
- Función de arranque en frío y función de carga con el sistema apagado
- Paneles LED seleccionables, panel multicolor

> ESPECIFICACIONES

Model	Z027			Z028		
Capacity	600 VA/ 360 W	800 VA/ 480 W	850 VA/ 510 W	1000 VA/ 600 W	1200 VA/ 720 W	1500 VA/ 900 W
Input						
Voltage	110 V/120 VAC or 220/230/240 VAC					
Voltage Range	81 to 145 VAC or 145 to 275 VAC					
Power Factor	≥ 0.99 @ 100% Load					
Frequency	60/50 Hz (Auto sensing)					
Output						
Voltage	110/120 VAC or 220/230/240 VAC					
Voltage Range	± 10%					
Frequency Range (Battery Mode)	60/50 ± 1 Hz					
Transfer Time	4 to 6 ms					
Wave Form (Battery Mode)	Simulated Sine Wave					
Battery						
Battery Model & Quantity	12 V/7 AH x 1	12 V/9 AH x 1	12 V/9 AH x 1	12 V/9 AH x 1	12 V/7 AH x 2	12 V/9 AH x 2
Charge Time	8 hours recover to 90% capacity					
Protection						
Full Protection	Discharge, Short circuit, Overload protection					
LED Indicator	Power indicator light, Charging, Battery inverter/malfunction					
Alarm						
Battery Mode	Sounding every 4 seconds					
Low Battery	Sounding every second					
Overload	Sounding every second					
Fault	Continuously sounding					
Interface						
USB/R232 Port (Optional)	Support windows XP/Vista, Windows 7/8, Linux, Unix, and MAC					
Optional SNMP	Power management from SNMP management and web browser					
Environment						
Humidity	0-90% RH @ 0-40 °C (Non-condensing)					
Noise Level	Less than 40 dB					
Dimension (mm)	320 x 90 x 140	320 x 90 x 140	320 x 90 x 140	320 x 90 x 140	365 x 140 x 165	365 x 140 x 165
Weight (kg)	5.3	5.8	5.8	5.8	9.9	12.6

