



### > CARACTERÍSTICAS

- Control inteligente de la CPU
- Reinicio automático mientras se recupera la corriente alterna
- Regulador de voltaje activo (AVR) con función de elevación y reducción para la estabilización del voltaje
- Función de arranque en frío y función de carga con el sistema apagado
- Paneles LED seleccionables, panel multicolor

### > ESPECIFICACIONES

| Model                          |   |                 | Z029            | Z030            |
|--------------------------------|---|-----------------|-----------------|-----------------|
| Capacity                       | 1200 VA/ 720 W  | 1500 VA/ 900 W  | 2000 VA/ 1200 W | 3000 VA/ 1800 W |
| <b>Input</b>                   |   |                 |                 |                 |
| Voltage                        | 110 V/120 VAC or 220/230/240 VAC  |                 |                 |                 |
| Voltage Range                  | 81 to 145 VAC or 145 to 275 VAC   |                 |                 |                 |
| Power Factor                   | ≥ 0.99 @ 100% Load  |                 |                 |                 |
| Frequency                      | 60/50 Hz (Auto sensing)   |                 |                 |                 |
| <b>Output</b>                  |   |                 |                 |                 |
| Voltage                        | 110/120 VAC or 220/230/240 VAC  |                 |                 |                 |
| Voltage Range                  | ± 10%   |                 |                 |                 |
| Frequency Range (Battery Mode) | 60/50 ± 1 Hz  |                 |                 |                 |
| Transfer Time                  | 4 to 6 ms   |                 |                 |                 |
| Wave Form (Battery Mode)       | Simulated Sine Wave   |                 |                 |                 |
| <b>Battery</b>                 |   |                 |                 |                 |
| Battery Model & Quantity       | 12 V/7 AH × 2   | 12 V/9 AH × 2   | 12 V/9 AH × 2   | 12 V/9 AH × 4   |
| Charge Time                    | 8 hours recover to 90% capacity   |                 |                 |                 |
| <b>Protection</b>              |   |                 |                 |                 |
| Full Protection                | Discharge, Short circuit, Overload protection   |                 |                 |                 |
| <b>Indicator</b>               |   |                 |                 |                 |
| LCD Display                    | AC mode, Battery mode, Load level, Battery level, Input voltage, Output voltage, Overload and low battery |                 |                 |                 |
| Battery Mode                   | Sounding every 4 seconds  |                 |                 |                 |
| Low Battery                    | Sounding every second   |                 |                 |                 |
| Overload                       | Sounding every second   |                 |                 |                 |
| Fault                          | Continuously sounding   |                 |                 |                 |
| <b>Interface</b>               |   |                 |                 |                 |
| USB/R232 Port (Optional)       | Support windows XP/Vista, Windows 7/8, Linux, Unix, and MAC   |                 |                 |                 |
| Optional SNMP                  | Power management from SNMP management and web browser   |                 |                 |                 |
| <b>Environment</b>             |   |                 |                 |                 |
| Humidity                       | 0-90% RH @ 0-40 °C (Non-condensing)   |                 |                 |                 |
| Noise Level                    | Less than 40 dB   |                 |                 |                 |
| Dimension (mm)                 | 365 × 140 × 165   | 365 × 140 × 165 | 365 × 140 × 165 | 395 × 145 × 210 |
| Weight (kg)                    | 9.9   | 12.6            | 13.2            | 18.9            |

